

1 Identification

- **Product identifier**
- **Product Name:** VOLATILE CAL STD
- **Part Number:** 624-MA
- **Application of the substance / the mixture** Certified Reference Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SPEX CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
- **Information department:** product safety department
- **Emergency telephone number:**
Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS06



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

methanol

benzene

carbon tetrachloride

1,1,2,2-tetrachloroethane

(Z)-1,3-dichloropropene

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H317 May cause an allergic skin reaction.

Product Name: VOLATILE CAL STD

(Contd. of page 1)

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)****HMS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients**Chemical characterization: Mixtures**

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-56-1	methanol	94.8%
75-35-4	1,1-dichloroethylene	0.2%
79-00-5	1,1,2-trichloroethane	0.2%
79-34-5	1,1,2,2-tetrachloroethane	0.2%
107-06-2	1,2-dichloroethane	0.2%
78-87-5	1,2-dichloropropane	0.2%
106-46-7	1,4-dichlorobenzene	0.2%
71-43-2	benzene	0.2%
75-27-4	bromodichloromethane	0.2%
56-23-5	carbon tetrachloride	0.2%
67-66-3	chloroform	0.2%
10061-01-5	(Z)-1,3-dichloropropene	0.2%
127-18-4	tetrachloroethylene	0.2%
108-88-3	toluene	0.2%
10061-02-6	trans-1,3-Dichloropropene	0.2%
79-01-6	trichloroethylene	0.2%
100-41-4	ethylbenzene	0.2%
75-09-2	dichloromethane	0.2%

Chemical identification of the substance/preparation

75-34-3	1,1-dichloroethane	0.2%
71-55-6	1,1,1-trichloroethane	0.2%
541-73-1	1,3-dichlorobenzene	0.2%
95-50-1	1,2-dichlorobenzene	0.2%
75-25-2	bromoform	0.2%
108-90-7	chlorobenzene	0.2%
156-59-2	cis-dichloroethylene	0.2%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 2)

124-48-1	dibromochloromethane	0.2%
156-60-5	trans-dichloroethylene	0.2%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** Do not induce vomiting; immediately call for medical help.

- **Information for Doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

67-56-1	methanol	530 ppm
75-34-3	1,1-dichloroethane	300 ppm
75-35-4	1,1-dichloroethylene	45 ppm
79-00-5	1,1,2-trichloroethane	30 ppm
79-34-5	1,1,2,2-tetrachloroethane	3 ppm
71-55-6	1,1,1-trichloroethane	230 ppm
541-73-1	1,3-dichlorobenzene	6 ppm
107-06-2	1,2-dichloroethane	50 ppm
78-87-5	1,2-dichloropropane	30 ppm
95-50-1	1,2-dichlorobenzene	50 ppm
106-46-7	1,4-dichlorobenzene	30 ppm
71-43-2	benzene	52 ppm
75-25-2	bromoform	1.5 ppm
75-27-4	bromodichloromethane	1.3 mg/m ³

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 3)

56-23-5	carbon tetrachloride	1.2 ppm
108-90-7	chlorobenzene	10 ppm
67-66-3	chloroform	2 ppm
156-59-2	cis-dichloroethylene	140 ppm
124-48-1	dibromochloromethane	1.1 mg/m ³
127-18-4	tetrachloroethylene	35 ppm
108-88-3	toluene	67 ppm
156-60-5	trans-dichloroethylene	280 ppm
79-01-6	trichloroethylene	130 ppm
100-41-4	ethylbenzene	33 ppm
75-09-2	dichloromethane	200 ppm

· PAC-2:

67-56-1	methanol	2,100 ppm
75-34-3	1,1-dichloroethane	670 ppm
75-35-4	1,1-dichloroethylene	500 ppm
79-00-5	1,1,2-trichloroethane	180 ppm
79-34-5	1,1,2,2-tetrachloroethane	120 ppm
71-55-6	1,1,1-trichloroethane	600 ppm
541-73-1	1,3-dichlorobenzene	66 ppm
107-06-2	1,2-dichloroethane	200 ppm
78-87-5	1,2-dichloropropane	220 ppm
95-50-1	1,2-dichlorobenzene	170 ppm
106-46-7	1,4-dichlorobenzene	170 ppm
71-43-2	benzene	800 ppm
75-25-2	bromoform	6.8 ppm
75-27-4	bromodichloromethane	14 mg/m ³
56-23-5	carbon tetrachloride	13 ppm
108-90-7	chlorobenzene	150 ppm
67-66-3	chloroform	64 ppm
156-59-2	cis-dichloroethylene	500 ppm
124-48-1	dibromochloromethane	12 mg/m ³
127-18-4	tetrachloroethylene	230 ppm
108-88-3	toluene	560 ppm
156-60-5	trans-dichloroethylene	1,000 ppm
79-01-6	trichloroethylene	450 ppm
100-41-4	ethylbenzene	1100* ppm
75-09-2	dichloromethane	560 ppm

· PAC-3:

67-56-1	methanol	7200* ppm
75-34-3	1,1-dichloroethane	4,000 ppm
75-35-4	1,1-dichloroethylene	1,000 ppm
79-00-5	1,1,2-trichloroethane	500 ppm
79-34-5	1,1,2,2-tetrachloroethane	150 ppm
71-55-6	1,1,1-trichloroethane	4,200 ppm
541-73-1	1,3-dichlorobenzene	400 ppm
107-06-2	1,2-dichloroethane	300 ppm
78-87-5	1,2-dichloropropane	2,000 ppm
95-50-1	1,2-dichlorobenzene	1,000 ppm
106-46-7	1,4-dichlorobenzene	1,000 ppm
71-43-2	benzene	4000* ppm
75-25-2	bromoform	41 ppm
75-27-4	bromodichloromethane	85 mg/m ³
56-23-5	carbon tetrachloride	340 ppm
108-90-7	chlorobenzene	400 ppm
67-66-3	chloroform	3,200 ppm

(Contd. on page 5)

Product Name: VOLATILE CAL STD

(Contd. of page 4)

156-59-2	cis-dichloroethylene	850 ppm
124-48-1	dibromochloromethane	73 mg/m ³
127-18-4	tetrachloroethylene	1,200 ppm
108-88-3	toluene	3700* ppm
156-60-5	trans-dichloroethylene	1,700 ppm
79-01-6	trichloroethylene	3,800 ppm
100-41-4	ethylbenzene	1800* ppm
75-09-2	dichloromethane	6,900 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

67-56-1 methanol	
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm
	Long-term value: 260 mg/m ³ , 200 ppm
	Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm
	Long-term value: 262 mg/m ³ , 200 ppm
	Skin; BEI
75-35-4 1,1-dichloroethylene	
REL	See Pocket Guide App.A
TLV	Long-term value: 20 mg/m ³ , 5 ppm
79-00-5 1,1,2-trichloroethane	
PEL	Long-term value: 45 mg/m ³ , 10 ppm
	Skin
REL	Long-term value: 45 mg/m ³ , 10 ppm
	Skin; See Pocket Guide Apps.A and C
TLV	Long-term value: 55 mg/m ³ , 10 ppm
	Skin
79-34-5 1,1,2,2-tetrachloroethane	
PEL	Long-term value: 35 mg/m ³ , 5 ppm
	Skin
REL	Long-term value: 7 mg/m ³ , 1 ppm
	Skin; See Pocket Guide Apps. A and C

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 5)

TLV	Long-term value: 6.9 mg/m ³ , 1 ppm Skin
107-06-2 1,2-dichloroethane	
PEL	Long-term value: 50 ppm Ceiling limit value: 100; 200* ppm *5-min peak in any 3 hrs
REL	Short-term value: 8 mg/m ³ , 2 ppm Long-term value: 4 mg/m ³ , 1 ppm See Pocket Guide Apps. A and C
TLV	Long-term value: 40 mg/m ³ , 10 ppm
78-87-5 1,2-dichloropropane	
PEL	Long-term value: 350 mg/m ³ , 75 ppm
REL	See Pocket Guide App. A
TLV	Long-term value: 46 mg/m ³ , 10 ppm DSEN
106-46-7 1,4-dichlorobenzene	
PEL	Long-term value: 450 mg/m ³ , 75 ppm
REL	See Pocket Guide App. A
TLV	Long-term value: 60 mg/m ³ , 10 ppm
71-43-2 benzene	
PEL	Short-term value: 15* mg/m ³ , 5* ppm Long-term value: 3* mg/m ³ , 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
REL	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
TLV	Short-term value: 8 mg/m ³ , 2.5 ppm Long-term value: 1.6 mg/m ³ , 0.5 ppm Skin; BEI
56-23-5 carbon tetrachloride	
PEL	Long-term value: 10 ppm Ceiling limit value: 25; 200* ppm *5-min peak in any 4 hrs
REL	Short-term value: 12.6* mg/m ³ , 2* ppm *60-min; See Pocket Guide App. A
TLV	Short-term value: 63 mg/m ³ , 10 ppm Long-term value: 31 mg/m ³ , 5 ppm Skin
67-66-3 chloroform	
PEL	Ceiling limit value: 240 mg/m ³ , 50 ppm
REL	Short-term value: 9.78* mg/m ³ , 2* ppm *60-min; See Pocket Guide App. A
TLV	Long-term value: 49 mg/m ³ , 10 ppm
127-18-4 tetrachloroethylene	
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 3 hrs
REL	Minimize workplace exp. concs.; Pocket Guide App. A
TLV	Short-term value: 685 mg/m ³ , 100 ppm Long-term value: 170 mg/m ³ , 25 ppm BEI
108-88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 6)

79-01-6 trichloroethylene

PEL Long-term value: 100 ppm
Ceiling limit value: 200; 300* ppm
*5-min peak in any 2 hrs

REL See Pocket Guide Apps. A and C

TLV Short-term value: 135 mg/m³, 25 ppm
Long-term value: 54 mg/m³, 10 ppm
BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm
BEI

75-09-2 dichloromethane

PEL Short-term value: 125 ppm
Long-term value: 25 ppm
see 29 CFR 1910.1052

REL See Pocket Guide App. A

TLV Long-term value: 174 mg/m³, 50 ppm
BEI

· Ingredients with biological limit values:**67-56-1 methanol**

BEI 15 mg/L
Medium: urine
Time: end of shift
Parameter: Methanol (background, nonspecific)

71-43-2 benzene

BEI 25 µg/g creatinine
Medium: urine
Time: end of shift
Parameter: S-Phenylmercapturic acid (background)

500 µg/g creatinine
Medium: urine
Time: end of shift
Parameter: t,t-Muconic acid (background)

127-18-4 tetrachloroethylene

BEI 3 ppm
Medium: end-exhaled air
Time: prior to shift
Parameter: Tetrachloroethylene

0.5 mg/L
Medium: blood
Time: prior to shift
Parameter: Tetrachloroethylene

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 8)

Product Name: VOLATILE CAL STD

(Contd. of page 7)

79-01-6 trichloroethylene

BEI 15 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Trichloroacetic acid (nonspecific)

0.5 mg/L

Medium: blood

Time: end of shift at end of workweek

Parameter: Trichloroethanol without hydrolysis (nonspecific)

-

Medium: blood

Time: end of shift at end of workweek

Parameter: Trichloroethylene (semi-quantitative)

-

Medium: end-exhaled air

Time: end of shift at end of workweek

Parameter: Trichloroethylene (semi-quantitative)

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

75-09-2 dichloromethane

BEI 0.3 mg/L

Medium: urine

Time: end of shift

Parameter: Dichloromethane (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 9)

Product Name: VOLATILE CAL STD

(Contd. of page 8)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)

· Flash point: 11 °C (51.8 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 455 °C (851 °F)

· Decomposition temperature: Not applicable.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	5.5 Vol %
Upper:	44 Vol %

· Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg)

· Density: Not applicable.

· Relative density: Not applicable.

· Vapor density: Not applicable.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not applicable.

· Viscosity:

Dynamic:	Not applicable.
Kinematic:	Not applicable.

· Solvent content:

Organic solvents:	97.4 %
VOC content:	96.80 %

Solids content: 0.4 %

· Other information: No further relevant information available.

10 Stability and reactivity

· Reactivity: No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions: No dangerous reactions known.

· Conditions to avoid: No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 10)

Product Name: VOLATILE CAL STD

(Contd. of page 9)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

67-56-1 methanol		
Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
79-34-5 1,1,2,2-tetrachloroethane		
Oral	LD50	800 mg/kg (rat)
71-55-6 1,1,1-trichloroethane		
Oral	LD50	10,300 mg/kg (rat)
107-06-2 1,2-dichloroethane		
Oral	LD50	670 mg/kg (rat)
Dermal	LD50	2,800 mg/kg (rat)
95-50-1 1,2-dichlorobenzene		
Oral	LD50	500 mg/kg (rat)
106-46-7 1,4-dichlorobenzene		
Oral	LD50	500 mg/kg (rat)
71-43-2 benzene		
Oral	LD50	4,894 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
Inhalative	LC50/4 h	9,980 mg/l (mouse)
56-23-5 carbon tetrachloride		
Oral	LD50	2,350 mg/kg (rat)
Dermal	LD50	5,070 mg/kg (rat)
79-01-6 trichloroethylene		
Oral	LD50	2,402 mg/kg (mouse)
Dermal	LD50	8,450 mg/kg (mouse)

- Primary irritant effect:

- on the skin: No irritant effect.

- on the eye: No irritating effect.

- Sensitization: No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Carcinogenic.

The product can cause inheritable damage.

- Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
75-35-4	1,1-dichloroethylene	3
79-00-5	1,1,2-trichloroethane	3
79-34-5	1,1,2,2-tetrachloroethane	2B
71-55-6	1,1,1-trichloroethane	3
541-73-1	1,3-dichlorobenzene	3
107-06-2	1,2-dichloroethane	2B
78-87-5	1,2-dichloropropane	1
95-50-1	1,2-dichlorobenzene	3
106-46-7	1,4-dichlorobenzene	2B
71-43-2	benzene	1
75-25-2	bromoform	3
75-27-4	bromodichloromethane	2B
56-23-5	carbon tetrachloride	2B
67-66-3	chloroform	2B
124-48-1	dibromochloromethane	3
127-18-4	tetrachloroethylene	2A
108-88-3	toluene	3

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 10)

79-01-6	trichloroethylene	I
100-41-4	ethylbenzene	2B
75-09-2	dichloromethane	2A
· NTP (National Toxicology Program)		
107-06-2	1,2-dichloroethane	R
106-46-7	1,4-dichlorobenzene	R
71-43-2	benzene	K
75-27-4	bromodichloromethane	R
56-23-5	carbon tetrachloride	R
67-66-3	chloroform	R
127-18-4	tetrachloroethylene	R
79-01-6	trichloroethylene	K
75-09-2	dichloromethane	R
· OSHA-Ca (Occupational Safety & Health Administration)		
71-43-2	benzene	
75-09-2	dichloromethane	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|---------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1230 |
| · UN proper shipping name | |
| · DOT | Methanol |
| · ADR | 1230 Methanol |
| · IMDG, IATA | METHANOL |

(Contd. on page 12)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 11)

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3, 6.1

· **ADR**



· **Class**

3 Flammable liquids

· **Label**

3+6.1

· **IMDG**



· **Class**

3 Flammable liquids

· **Label**

3/6.1

· **IATA**



· **Class**

3 Flammable liquids

· **Label**

3 (6.1)

· **Packing group**

· **DOT, ADR, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

336

· **EMS Number:**

F-E,S-D

· **Stowage Category**

B

· **Stowage Code**

SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC**

Code

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)**

IL

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1230 METHANOL, 3 (6.1), II

US

(Contd. on page 13)

Product Name: VOLATILE CAL STD

(Contd. of page 12)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 313 (Specific toxic chemical listings):

67-56-1	methanol
75-34-3	1,1-dichloroethane
75-35-4	1,1-dichloroethylene
79-00-5	1,1,2-trichloroethane
79-34-5	1,1,2,2-tetrachloroethane
71-55-6	1,1,1-trichloroethane
541-73-1	1,3-dichlorobenzene
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
95-50-1	1,2-dichlorobenzene
106-46-7	1,4-dichlorobenzene
71-43-2	benzene
75-25-2	bromoform
75-27-4	bromodichloromethane
56-23-5	carbon tetrachloride
108-90-7	chlorobenzene
67-66-3	chloroform
127-18-4	tetrachloroethylene
108-88-3	toluene
10061-02-6	trans-1,3-Dichloropropene
79-01-6	trichloroethylene
100-41-4	ethylbenzene
75-09-2	dichloromethane

· TSCA (Toxic Substances Control Act):

67-56-1	methanol
75-34-3	1,1-dichloroethane
75-35-4	1,1-dichloroethylene
79-00-5	1,1,2-trichloroethane
79-34-5	1,1,2,2-tetrachloroethane
71-55-6	1,1,1-trichloroethane
541-73-1	1,3-dichlorobenzene
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
95-50-1	1,2-dichlorobenzene
106-46-7	1,4-dichlorobenzene
71-43-2	benzene
75-25-2	bromoform
75-27-4	bromodichloromethane
56-23-5	carbon tetrachloride
108-90-7	chlorobenzene
67-66-3	chloroform
156-59-2	cis-dichloroethylene
124-48-1	dibromochloromethane
127-18-4	tetrachloroethylene
108-88-3	toluene
156-60-5	trans-dichloroethylene
10061-02-6	trans-1,3-Dichloropropene
79-01-6	trichloroethylene
100-41-4	ethylbenzene
75-09-2	dichloromethane

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 13)

· TSCA new (21st Century Act) (Substances not listed)	
75-27-4	bromodichloromethane
10061-01-5	(Z)-1,3-dichloropropene
10061-02-6	trans-1,3-Dichloropropene

· Proposition 65

· Chemicals known to cause cancer:	
75-34-3	1,1-dichloroethane
79-00-5	1,1,2-trichloroethane
79-34-5	1,1,2,2-tetrachloroethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
106-46-7	1,4-dichlorobenzene
71-43-2	benzene
75-25-2	bromoform
75-27-4	bromodichloromethane
56-23-5	carbon tetrachloride
67-66-3	chloroform
127-18-4	tetrachloroethylene
79-01-6	trichloroethylene
100-41-4	ethylbenzene
75-09-2	dichloromethane

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

71-43-2	benzene
79-01-6	trichloroethylene

· Chemicals known to cause developmental toxicity:

67-56-1	methanol
71-43-2	benzene
67-66-3	chloroform
108-88-3	toluene
79-01-6	trichloroethylene

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
75-34-3	1,1-dichloroethane	C
75-35-4	1,1-dichloroethylene	C, S (inh.), I (oral)
79-00-5	1,1,2-trichloroethane	C
79-34-5	1,1,2,2-tetrachloroethane	L
71-55-6	1,1,1-trichloroethane	II
541-73-1	1,3-dichlorobenzene	D
107-06-2	1,2-dichloroethane	B2
95-50-1	1,2-dichlorobenzene	D
71-43-2	benzene	A, K/L
75-25-2	bromoform	B2
75-27-4	bromodichloromethane	B2
56-23-5	carbon tetrachloride	L
108-90-7	chlorobenzene	D
67-66-3	chloroform	B2, L, NL
156-59-2	cis-dichloroethylene	II
124-48-1	dibromochloromethane	C
127-18-4	tetrachloroethylene	L
108-88-3	toluene	II
156-60-5	trans-dichloroethylene	II
79-01-6	trichloroethylene	CaH
100-41-4	ethylbenzene	D

(Contd. on page 15)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 14)

75-09-2	dichloromethane	L
· TLV (Threshold Limit Value established by ACGIH)		
75-34-3	1,1-dichloroethane	A4
75-35-4	1,1-dichloroethylene	A4
79-00-5	1,1,2-trichloroethane	A3
79-34-5	1,1,2,2-tetrachloroethane	A3
71-55-6	1,1,1-trichloroethane	A4
107-06-2	1,2-dichloroethane	A4
78-87-5	1,2-dichloropropane	A4
95-50-1	1,2-dichlorobenzene	A4
106-46-7	1,4-dichlorobenzene	A3
71-43-2	benzene	A1
75-25-2	bromoform	A3
56-23-5	carbon tetrachloride	A2
108-90-7	chlorobenzene	A3
67-66-3	chloroform	A3
127-18-4	tetrachloroethylene	A3
108-88-3	toluene	A4
79-01-6	trichloroethylene	A2
100-41-4	ethylbenzene	A3
75-09-2	dichloromethane	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

75-35-4	1,1-dichloroethylene
79-00-5	1,1,2-trichloroethane
79-34-5	1,1,2,2-tetrachloroethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
106-46-7	1,4-dichlorobenzene
71-43-2	benzene
56-23-5	carbon tetrachloride
67-66-3	chloroform
127-18-4	tetrachloroethylene
79-01-6	trichloroethylene
75-09-2	dichloromethane

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms

· **Signal word** Danger

· Hazard-determining components of labeling:

methanol

benzene

carbon tetrachloride

1,1,2,2-tetrachloroethane

(Z)-1,3-dichloropropene

· Hazard statements

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 16)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/12/2018

Reviewed on 01/12/2018

Product Name: VOLATILE CAL STD

(Contd. of page 15)

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

· **Date of preparation / last revision** 01/12/2018 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LCS0: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1A: Carcinogenicity – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2