### 1 Identification

- · Product identifier
- · Product Name: VOA Additional Analytes Mix D (High Level)
- · Part Number: 8240-DH
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

(

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

methanol

carbon disulphide

· Hazard statements

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

 $Dispose\ of\ contents/container\ in\ accordance\ with\ local/regional/national/international\ regulations.$ 

(Contd. on page 2)

(Contd. of page 1)

Printing date 05/24/2018 Reviewed on 05/24/2018

Product Name: VOA Additional Analytes Mix D (High Level)

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions

	on: Mixiure of the substances tisted below with honnazardous additions.	
0	us components:	
67-56-1	methanol	98.49
591-78-6	hexan-2-one	0.2%
108-10-1	4-methylpentan-2-one	0.29
75-15-0	carbon disulphide	0.2%
100-42-5	styrene	0.29
· Chemical	l identification of the substance/preparation	
110-75-8	2-chloroethyl vinyl ether	0.29
67-64-1	acetone	0.29
106-42-3	p-xylene	0.29
78-93-3	butanone	0.24

### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; immediately call for medical help.

Do not give anything to eat or drink - Do not induce vomitting

- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Product Name: VOA Additional Analytes Mix D (High Level)

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
67-56-1	methanol	530 ppm
110-75-8	2-chloroethyl vinyl ether	0.16 ppm
591-78-6	hexan-2-one	10 ppm
67-64-1		200 ppm
108-10-1	4-methylpentan-2-one	75 ppm
75-15-0	carbon disulphide	13 ppm
100-42-5	styrene	20 ppm
78-93 <i>-3</i>	butanone	200 ppm
· PAC-2:		
67-56-1	methanol	2,100 ppm
110-75-8	2-chloroethyl vinyl ether	1.8 ppm
591-78-6	hexan-2-one	830 ppm
67-64-1	acetone	3200* ppn
	4-methylpentan-2-one	500 ppm
75-15-0	carbon disulphide	160 ppm
100-42-5		130 ppm
78-93 <i>-</i> 3	butanone	2700* ppn
· PAC-3:		
67-56-1	methanol	7200* ppn
110-75-8	2-chloroethyl vinyl ether	11 ppm
591-78-6	hexan-2-one	5000* ppn
67-64-1	acetone	5700* ppn
108-10-1	4-methylpentan-2-one	3000* ppn
	carbon disulphide	480 ppm
100-42-5		1100* ррг
78-93-3	butanone	4000* ppn

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 4)

Product Name: VOA Additional Analytes Mix D (High Level)

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

#### · Components with limit values that require monitoring at the workplace:

#### 67-56-1 methanol

- PEL Long-term value: 260 mg/m³, 200 ppm
- REL Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm

Skin

TLV Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm

Skin; BEI

#### 591-78-6 hexan-2-one

- PEL Long-term value: 410 mg/m³, 100 ppm
- REL Long-term value: 4 mg/m³, 1 ppm
- TLV Short-term value: 40 mg/m³, 10 ppm Long-term value: 20 mg/m³, 5 ppm Skin, BEI

#### 108-10-1 4-methylpentan-2-one

- PEL Long-term value: 410 mg/m³, 100 ppm
- REL Short-term value: 300 mg/m³, 75 ppm
  - Long-term value: 205 mg/m³, 50 ppm
- TLV Short-term value: 307 mg/m³, 75 ppm Long-term value: 82 mg/m³, 20 ppm BEI

### 75-15-0 carbon disulphide

- PEL Long-term value: 20 ppm
  - Ceiling limit value: 30; 100\* ppm \*30-min peak per 8-hr shift
- REL Short-term value: 30 mg/m³, 10 ppm Long-term value: 3 mg/m³, 1 ppm
  - Skin
- TLV Long-term value: 3.13 mg/m³, 1 ppm Skin, BEI

#### 100-42-5 styrene

- PEL Long-term value: 100 ppm
  - Ceiling limit value: 200; 600\* ppm \*5-min peak in any 3 hrs
- REL Short-term value: 425 mg/m³, 100 ppm
  - Long-term value: 215 mg/m³, 50 ppm
- TLV Short-term value: 170 mg/m³, 40 ppm Long-term value: 85 mg/m³, 20 ppm

## · Ingredients with biological limit values:

#### 67-56-1 methanol

BEI 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

(Contd. on page 5)

Product Name: VOA Additional Analytes Mix D (High Level)

(Contd. of page 4)

#### 591-78-6 hexan-2-one

BEI 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2.5-Hexanedione without hydrolysis

#### 108-10-1 4-methylpentan-2-one

BEI 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

#### 75-15-0 carbon disulphide

BEI 0.5 mg/g creatinine

Medium: urine Time: end of shift

Parameter: 2-Thioxothiazolidine-4-carboxylic acid (background, nonspecific)

#### 100-42-5 styrene

BEI 400 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

0.2 mg/L

Medium: venous blood Time: end of shift

Parameter: Styrene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

6)

Product Name: VOA Additional Analytes Mix D (High Level)

(Contd. of page 5)

9 Physical and chemical propertion	es
· Information on basic physical and	chemical properties
· General Information	themical properties
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odour Threshold:	Not applicable.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)
· Flash point:	< 23 °C (<73.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	455 °C (851 °F)
· Decomposition temperature:	Not applicable.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
· Density at 20 °C (68 °F)	0.79192-0.79193 g/cm³ (6.60857-6.60866 lbs/gal)
Relative density	Not applicable.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not applicable.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	99.4 %
VOC content:	99.20 %
Solids content:	0.0 %
· Other information	No further relevant information available.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot \textit{Conditions to avoid No further relevant information available}.$
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values that a	are relevant fo	or classification:

# 67-56-1 methanol

Oral LD50 5,628 mg/kg (rat)

Dermal LD50 15,800 mg/kg (rabbit)

(Contd. on page 7)

(Contd. of page 6)

Printing date 05/24/2018 Reviewed on 05/24/2018

#### Product Name: VOA Additional Analytes Mix D (High Level)

75-15-0 carbon disulphide

Oral LD50 3,188 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 $The \ product \ shows \ the \ following \ dangers \ according \ to \ internally \ approved \ calculation \ methods \ for \ preparations:$ 

Toxic

· Carcinogenic categories

Carcinogenic categories		
· IARC (International Agency for Research on Cancer)		
108-10-1 4-methylpentan-2-one	28	
106-42-3 p-xylene	3	
100-42-5 styrene	28	
NTP (National Toxicology Program)		
100-42-5 styrene R		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

# 14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN1230
- · UN proper shipping name
- ⋅ DOT
   Methanol

   ⋅ ADR
   1230 Methanol

   ⋅ IMDG, IATA
   METHANOL
- · Transport hazard class(es)
- $\cdot DOT$





· Class 3 Flammable liquids

(Contd. on page 8)

Product Name: VOA Additional Analytes Mix D (High Level)

	(Contd. of page
· Label	3, 6.1
ADR	
· Class · Label	3 Flammable liquids 3+6.1
· IMDG	
· Class · Label	3 Flammable liquids 3/6.1
· IATA  · Class	3 Flammable liquids
· Label · Packing group	3 (6.1)
DOT, ADR, IMDG, IATA	II
Environmental hazards: Special precautions for user Danger code (Kemler): EMS Number: Stowage Category Stowage Code	Not applicable.  Warning: Flammable liquids 336 F-E,S-D B SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARF	
Transport/Additional information:	пот аррисаон.
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1230 METHANOL, 3 (6.1), II

# 15 Regulatory information

- $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

	· Sara		
	· Section 313 (Specific toxic chemical listings):		
		methanol	
		4-methylpentan-2-one	
Г		carbon disulphide	
Γ	106-42-3		
Γ	100-42-5		
	<i>78-93-3</i>	butanone	
_		(Contd on page 9)	

Product Name: VOA Additional Analytes Mix D (High Level)

(Contd. of page 8) · TSCA (Toxic Substances Control Act): All ingredients are listed. · TSCA new (21st Century Act) (Substances not listed) 591-78-6 hexan-2-one Proposition 65 · Chemicals known to cause cancer: 108-10-1 4-methylpentan-2-one 100-42-5 styrene · Chemicals known to cause reproductive toxicity for females: 75-15-0 carbon disulphide · Chemicals known to cause reproductive toxicity for males: 591-78-6 hexan-2-one 75-15-0 carbon disulphide · Chemicals known to cause developmental toxicity: 67-56-1 methanol 591-78-6 hexan-2-one 108-10-1 4-methylpentan-2-one 75-15-0 carbon disulphide · Carcinogenic categories · EPA (Environmental Protection Agency) 591-78-6 hexan-2-one II 67-64-1 acetone Ι

- 106-42-3 p-xylene 78-93-3 butanone
- TLV (Threshold Limit Value established by ACGIH)

   67-64-1 acetone
   A4

   75-15-0 carbon disulphide
   A4

   106-42-3 p-xylene
   A4

   100-42-5 styrene
   A4
- · NIOSH-Ca (National Institute for Occupational Safety and Health)

  None of the ingredients is listed.
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





108-10-1 4-methylpentan-2-one



GHS02

GHS06

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

methanol

carbon disulphide

· Hazard statements

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

Ι

Product Name: VOA Additional Analytes Mix D (High Level)

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 05/24/2018 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity – Category 3

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2 STOT SE 1: Specific target organ toxicity (single exposure) – Category I

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2