



Reviewed on 11/20/2023

1 Identification

- · Product identifier
- · Product Name: 1000 µg/mL Beryllium
- · Part Name:
- CLBE2-2Y
- CLBE2-2M
- · Application of the substance / the mixture For Laboratory Use Only
- · Uses advised against Not for Human or Animal Use
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Spex CertiPrep, LLC. 203 Norcross Ave, Metuchen, NJ 08840 USA 732-549-7144 USMet-CRMSales@antylia.com
- · Information department: product safety department · Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)
- Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 1A H350 May cause cancer.



Skin Irritation 2 H315 Causes skin irritation

- Eye Irritation 2A H319 Causes serious eye irritation.
- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labeling:
- beryllium acetate
- · Hazard statements
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H350 May cause cancer.
- · Precautionary statements
- Obtain special instructions before use. P201 P202 Do not handle until all safety precautions have been read and understood. P264 Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. P280 P302 + P352If on skin: Wash with plenty of water. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention.
- Specific treatment (see on this label). P321
- P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313
- If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P405 Store locked up. P501
 - Dispose of contents/container in accordance with local/regional/national/international regulations.



Product Name: 1000 µg/mL Beryllium

- · Classification system:
- · NFPA ratings (scale 0 4)



Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH *2 Health = *2FIRE 0 Fire = 0Reactivity = 0**REACTIVITY** 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

7697-37-2 nitric acid

543-81-7 beryllium acetate

· Chemical identification of the substance/preparation

7732-18-5 water, distilled, conductivity or of similar purity

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

Safety Data Sheet

acc. to OSHA HCS

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:
- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

7697-37-2 nitric acid

Page 2/7

2.0%

1.1%

96.9%

Reviewed on 11/20/2023

(Contd. of page 1)



Product Name: 1000 µg/mL Beryllium

Reviewed on 11/20/2023

Page 3/7

	(Contd. of page 2)
· PAC-2:	
7697-37-2 nitric acid	24 ppm
· PAC-3:	
7697-37-2 nitric acid	92 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

- · Components with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin. • **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance: Form:

Liquid

Product Name: 1000 µg/mL Beryllium

Page 4/7

Reviewed on 11/20/2023	Reviewed	on	11	1/2	0/	20	92	3
------------------------	----------	----	----	-----	----	----	----	---

		(Contd. of page 3)
Color:	According to product specification	
· Odor:	Characteristic	
· Odour Threshold:	Not applicable.	
· pH-value:	Not applicable.	
• Change in condition	Undetermined.	
Melting point/Melting range: Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
• Decomposition temperature:	Not applicable.	
· Ignition temperature:	Product is not selfigniting.	
• Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not applicable.	
Upper:	Not applicable.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density	Not applicable.	
· Relative density	Not applicable.	
· Vapor density	Not applicable.	
· Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	er): Not applicable.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Water:	96.9 % 9.9.9 %	
VOC content:	0.00 %	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
543-81-7 beryllium acetate	1
·NTP (National Toxicology Program)	
543-81-7 beryllium acetate	K
	(Contd. on page 5)
	US

Product Name: 1000 µg/mL Beryllium

(Contd. of page 4)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information · UN-Number · DOT, ADR, IMDG, IATA UN3264 · UN proper shipping name $\cdot DOT$ Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) · ADR 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) · IMDG, IATA CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) · Transport hazard class(es) $\cdot DOT$ · Class 8 Corrosive substances · Lahel 8 · ADR, IMDG, IATA 8 Corrosive substances · Class · Label 8 · Packing group · DOT, ADR, ÎMDG, IATA Ш · Environmental hazards: Not applicable. · Special precautions for user Warning: Corrosive substances · Hazard identification number (Kemler code): 80 · EMS Number: F-A, S-B· Segregation groups (SGG1) Acids · Stowage Category Α

Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/20/2023

Page 5/7

Page 6/7

Product Name: 1000 µg/mL Beryllium

	(Contd. of page 5)
· Stowage Code · Segregation Code	SW2 Clear of living quarters. SG36 Stow "separated from" SGG18-alkalis. SG49 Stow "separated from" SGG6-cyanides
· Transport in bulk according to Annex II of MARPOL73/78 an	the IBC Code Not applicable.
· Transport/Additional information:	
• ADR • Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara	
· Section 313 (Specific toxic chemical listings):	
7697-37-2 nitric acid	
543-81-7 beryllium acetate	
· TSCA (Toxic Substances Control Act):	
7732-18-5 water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2 nitric acid	ACTIVE
· Hazardous Air Pollutants	
None of the ingredients is listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
543-81-7 beryllium acetate	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value)	
None of the ingredients is listed.	

• NIOSH-Ca (National Institute for Occupational Safety and Health)

543-81-7 beryllium acetate

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

beryllium acetate

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Product Name: 1000 µg/mL Beryllium

Reviewed on 11/20/2023

H350 May cause c	ancer.	-
· Precautionary stat	<i>tements</i>	
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
P264	Wash thoroughly after handling.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P302+P352	If on skin: Wash with plenty of water.	
P305+P351+P338	3 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P321	Specific treatment (see on this label).	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

· Contact:

Spex CertiPrep, LLC. 1-732-549-7144 · Date of preparation / last revision 11/20/2023 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Carcinogenicity 1A: Carcinogenicity – Category 1A

Page 7/7

US -