Printing date 06/27/2023 Reviewed on 06/27/2023

1 Identification

- · Product identifier
- · Product Name: Volatiles Mix D (High Level)
- · Part Name: CLPV-D90H
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Spex CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA 732-549-7144

USMet-CRMSales@antylia.com

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Inhalation 3 H331 Toxic if inhaled.



Carcinogenicity 1B

H350 May cause cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 1

H370 Causes damage to the central nervous system and the visual organs.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to the central nervous system, the kidneys and the cardiovascular system through prolonged or repeated exposure.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS06

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

methanol

styrene

carbon disulphide

4-methylpentan-2-one

· Hazard statements

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to the central nervous system and the visual organs.

H373 May cause damage to the central nervous system, the kidneys and the cardiovascular system through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

(Contd. of page 1)

Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1 Fire = 3Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

7		
· Dangeroi	s components:	
67-56-1	methanol	98.4%
75-15-0	carbon disulphide	0.2%
100-42-5	styrene	0.2%
108-10-1	4-methylpentan-2-one	0.2%
591-78-6	hexan-2-one	0.2%
· Chemical	identification of the substance/preparation	
67-64-1	acetone	0.2%
78-93-3	butanone	0.2%

4 First-aid measures

106-42-3 p-xylene

· Description of first aid measures

156-59-2 cis-dichloroethylene

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

0.2%

0.2%



Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

• PAC-1:	v	
	methanol	530 ppm
67-64-1	acetone	200 ppm
75-15-0	carbon disulphide	13 ppm
	butanone	200 ppm
100-42-5	styrene	20 ppm
	4-methylpentan-2-one	75 ppm
	cis-dichloroethylene	140 ppm
591-78-6	hexan-2-one	10 ppm
· PAC-2:		
67-56-1	methanol	2,100 ppm
67-64-1		3200* ppm
75-15-0	carbon disulphide	160 ррт
78-93-3	butanone	2700* ppm
100-42-5		130 ррт
108-10-1	4-methylpentan-2-one	500 ppm
156-59-2	cis-dichloroethylene	500 ppm
591-78-6	hexan-2-one	830 ppm
· PAC-3:		
67-56-1	methanol	7200* ppm
67-64-1	acetone	5700* ppm
75-15-0	carbon disulphide	480 ppm
78-93-3	butanone	4000* ppm
100-42-5	styrene	1100* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
156-59-2	cis-dichloroethylene	850 ppm
591-78-6	hexan-2-one	5000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

 $Open\ and\ handle\ receptacle\ with\ care.$

 $Prevent\ formation\ of\ aerosols.$

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

(Contd. of page 3)

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.

· Cont	rol parameters
· Com	ponents with limit values that require monitoring at the workplace:
	6-1 methanol
PEL	Long-term value: 260 mg/m³, 200 ppm
	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
75-1:	5-0 carbon disulphide
PFI	Long-term value: 20 npm

PEL Long-term value: 20 ppm Ceiling limit value: 30; 100* ppm *30-min peak per 8-hr shift REL Short-term value: 30 mg/m³, 10 ppm

Long-term value: 3 mg/m³, 1 ppm Skin

TLVLong-term value: 1 ppm Skin, BEI, A4

100-42-5 styrene

PEL Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs

REL Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm Short-term value: 20 ppm

Long-term value: 10 ppm BEI, OTO, A3

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm REL Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm Short-term value: 75 ppm

Long-term value: 20 ppm BEI, A3

591-78-6 hexan-2-one

PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 4 mg/m³, 1 ppm TLV Short-term value: 10 ppm Long-term value: 5 ppm

Ingredients with biological limit values:

67-56-1 methanol

Skin

BEI 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

(Contd. on page 5)



Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

(Contd. of page 4)

75-15-0 carbon disulphide

BEI 0.5 mg/g creatinine

Medium: urine Time: end of shift

Parameter: 2-Thioxothiazolidine-4-carboxylic acid (background, nonspecific)

100-42-5 styrene

BEI 400 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

40 μg/L Medium: urine Time: end of shift Parameter: Styrene

108-10-1 4-methylpentan-2-one

BEI 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

591-78-6 hexan-2-one

BEI 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2.5-Hexanedione without hydrolysis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

Odor: CharacteristicOdour Threshold: Not applicable.

(Contd. on page 6)



Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

(Contd. of page 5)

	(Contd. of page 5
· pH-value:	Not applicable.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 64.7 °C (148.5 °F)
· Flash point:	< 23 °C (< 73.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Ignition temperature:	455 °C (851 °F)
· Decomposition temperature:	Not applicable.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	5.5 Vol % 44 Vol %
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
 Density at 20 °C (68 °F) Relative density Vapor density Evaporation rate 	0.79238-0.79239 g/cm³ (6.61241-6.61249 lbs/gal) Not applicable. Not applicable. Not applicable.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/wate	er): Not applicable.
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.
Solvent content: Organic solvents: VOC content:	99.6 % 99.40 %
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- $\cdot \textit{Reactivity No further relevant information available}.$
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- $\cdot \textbf{\textit{Possibility of hazardous reactions}} \ \textit{No dangerous reactions known}.$
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	· LD/LC50 values that are relevant for classification:	
67-56-1	67-56-1 methanol	
Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

- · Primary irritant effect:
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Product is suspected to cause damage to fertility.

Product is suspected to cause birth defects.

(Contd. on page 7)



Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

(Contd. of page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
100-42-5 styrene	2A
106-42-3 p-xylene	3
108-10-1 4-methylpentan-2-one	2 <i>B</i>
· NTP (National Toxicology Program)	
100-42-5 styrene	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $. \textit{\textbf{Bioaccumulative potential No further relevant information available}. \\$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA UN1230 · UN proper shipping name

 $\cdot DOT$

Methanol 1230 METHANOL $\cdot ADR$ · IMDG, IATA **METHANOL**

· Transport hazard class(es)

 $\cdot DOT$



· Class 3 Flammable liquids

· Label 3, 6.1

 $\cdot ADR$



Class 3 Flammable liquids

(Contd. on page 8)

(Contd. of page 7)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

· Label 3+6.1

 \cdot IMDG



3 Flammable liquids · Class \cdot Label 3/6.1

 \cdot IATA





3 Flammable liquids · Class · Label 3(6.1)

· Packing group

· DOT, ADR, IMDG, IATA II

Not applicable. · Environmental hazards:

· Special precautions for user Warning: Flammable liquids 336

· Hazard identification number (Kemler code): · EMS Number: F-E,S-DВ · Stowage Category

· Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot ADR$

Code: E2 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

 \cdot IMDG

1L· Limited quantities (LQ) · Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1230 METHANOL, 3 (6.1), II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 313 (Specific toxic chemical listings): 67-56-1 methanol

75-15-0 carbon disulphide

100-42-5 styrene

106-42-3 p-xylene

108-10-1 4-methylpentan-2-one

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

67-56-1 methanol

75-15-0 carbon disulphide

100-42-5 styrene

106-42-3 p-xylene

108-10-1 4-methylpentan-2-one

Proposition 65

Chemicals known to cause cancer:

100-42-5 styrene

Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

· Carcinogenic categories

Curcinogenic tutegories		
· EPA (En	vironmental Protection Agency)	
67-64-1	acetone	I
78-93-3	butanone	I
	p-xylene	I
108-10-1	4-methylpentan-2-one	I
156-59-2	cis-dichloroethylene	II
591-78-6	hexan-2-one	II
· TLV (Thr	eshold Limit Value)	
67-64-1	acetone	A4
75-15-0	carbon disulphide .	A4
100-42-5	styrene	A4
106-42-3	p-xylene .	A4
· NIOSH-C	Ta (National Institute for Occupational Safety and Health)	_

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





None of the ingredients is listed.



GHS02

GHS06

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

methanol

styrene

carbon disulphide

4-methylpentan-2-one

· Hazard statements

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to the central nervous system and the visual organs.

H373 May cause damage to the central nervous system, the kidneys and the cardiovascular system through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.



Printing date 06/27/2023 Reviewed on 06/27/2023

Product Name: Volatiles Mix D (High Level)

(Contd. of page 9)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

Spex CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 06/27/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Inhalation 3: Acute toxicity – Category 3

Carcinogenicity 1B: Carcinogenicity – Category 1B
Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) - Category 1
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2