Page 1/11

1 Identification

- · Product identifier
- Product Name: <u>TCLP Calibration/Spiking Mix</u>
- · Part Number: ECS-A-018
- · Application of the substance / the mixture Certified Reference Material
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: SPEX CertiPrep, LLC.
 203 Norcross Ave, Metuchen, NJ 08840 USA
- Information department: product safety department • Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H350 May cause cancer.

H360 May damage fertility or the unborn child.

Carc. 1B Repr. 1



Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: dichloromethane nitrobenzene bis(2-chloroethyl) ether 2,4-dinitrotoluene Hazard statements
- H225 Highly flammable liquid and vapor. H302 Harmful if swallowed. H350 May cause cancer. H360 May damage fertility or the unborn child.
- · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

· Classification system: · NFPA ratings (scale 0 - 4)	(Contd. of page 1)
$\begin{array}{c} \textbf{Health} = 1\\ Fire = 3\\ Reactivity = 0 \end{array}$	
· HMIS-ratings (scale 0 - 4)	
HEALTH*1FIRE3Fire = 3REACTIVITY \bigcirc	
Other hazards	
· Results of PBT and vPvB assessment	
• PBT: 87-68-3 hexachlorobuta-1,3-diene	
· vPvB:	
87-68-3 hexachlorobuta-1,3-diene	

3 Composition/information on ingredients

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerou	is components:	
	9-2 dichloromethane	
	2,4,5-trichlorophenol	0.2%
88-06-2	2,4,6-trichlorophenol	0.2%
	2,4-dinitrotoluene	0.2%
111-44-4	bis(2-chloroethyl) ether	0.2%
118-74-1	hexachlorobenzene	0.2%
87-68-3	hexachlorobuta-1,3-diene	0.2%
67-72-1	hexachloroethane	0.2%
98-95-3	nitrobenzene	0.2%
87-86-5	pentachlorophenol	0.2%
106-46-7	1,4-dichlorobenzene	0.2%
· Chemica	l identification of the substance/preparation	
95-48-7	o-cresol	0.2%
	3-Methylphenol	0.2%
106-44-5	p-cresol	0.2%
108-95-2	1	0.2%
110-86-1	Nitrogen (from Pyridine)	0.2%

4 First-aid measures

- · Description of first aid measures
- General information: Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. • After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing:

- Immediately call a doctor.
- Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

(Contd. of page 2)

Reviewed on 03/28/2018

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

	nental precautions: How product to reach sewage system or any water course.	
Inform re	spective authorities in case of seepage into water course or sewage system.	
Do not al	low to enter sewers/ surface or ground water.	
	and material for containment and cleaning up:	
	ith liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). contaminated material as waste according to item 13.	
	dequate ventilation.	
Reference	e to other sections	
	on 7 for information on safe handling.	
	on 8 for information on personal protection equipment. on 13 for disposal information.	
	e Action Criteria for Chemicals	
PAC-1:		
	dichloromethane	200 ppm
	2,4,5-trichlorophenol	2.5 mg/m ³
	2,4,6-trichlorophenol	2.5 mg/m ³
	2,4-dinitrotoluene	0.6 mg/m ³
	bis(2-chloroethyl) ether	10 ppm
	hexachlorobenzene	0.006 mg/
	hexachlorobuta-1,3-diene	1 ppm
	hexachloroethane	3 ppm
	nitrobenzene	3 ppm
	pentachlorophenol	1 mg/m ³
108-95-2		15 ppm
	Nitrogen (from Pyridine)	3 ppm
	1,4-dichlorobenzene	30 ppm
PAC-2:		
	dichloromethane	560 pp
	2,4,5-trichlorophenol	27 mg/
	2,4,6-trichlorophenol	27 mg/ 27 mg/
	2,4-dinitrotoluene	12 mg/
	bis(2-chloroethyl) ether	25 ppn
	hexachlorobenzene	23 pp/ 14 mg/
	hexachlorobuta-1,3-diene	3 ppm
	hexachloroethane	36 ppn
	nitrobenzene	20 ppn
	pentachlorophenol	20 ppn 15 mg/
108-95-2		23 ppn
	Nitrogen (from Pyridine)	23 ppn 19 ppn
	1,4-dichlorobenzene	170 pp
PAC-3:		110 pp
	dichloromethane	6 000 m
	2,4,5-trichlorophenol	6,900 pp 160 mg/r
	2,4,5-trichlorophenol 2,4,6-trichlorophenol	160 mg/i 160 mg/i
	2,4,0-trichlorophenol 2,4-dinitrotoluene	200 mg/i
121 11 2	2,4- מוחנורטוטועפונפ	200 mg/1
	bis(2-chloroethyl) ether	250 mg/

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2018

Reviewed on 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

	(Cor	ntd. of page 3)
87-68-3	hexachlorobuta-1,3-diene	10 ppm
	hexachloroethane	300 ppm
	nitrobenzene	200 ppm
	pentachlorophenol	150 mg/m ³
108-95-2		200 ppm
	Nitrogen (from Pyridine)	3600* ppm
106-46-7	1,4-dichlorobenzene	1,000 ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

75-0	9-2 dichloromethane
PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m³, 50 ppm BEI
111-	44-4 bis(2-chloroethyl) ether
PEL	Ceiling limit value: 90 mg/m³, 15 ppm Skin
REL	Short-term value: 60 mg/m³, 10 ppm Long-term value: 30 mg/m³, 5 ppm Skin; See Pocket Guide App. A
TLV	Short-term value: 58 mg/m³, 10 ppm Long-term value: 29 mg/m³, 5 ppm Skin
118-	74-1 hexachlorobenzene
TLV	Long-term value: 0.002 mg/m ³ Skin
87-6	8-3 hexachlorobuta-1,3-diene
REL	Long-term value: 0.24 mg/m ³ , 0.02 ppm Skin; See Pocket Guide App. A
TLV	Long-term value: 0.21 mg/m³, 0.02 ppm Skin
67-7.	2-1 hexachloroethane
PEL	Long-term value: 10 mg/m³, 1 ppm Skin
REL	Long-term value: 10 mg/m³, 1 ppm Skin; See Pocket Guide Apps. A and C
	(Contd. on page 5)

us -

US

Printing date 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

Reviewed on 03/28/2018

Trounci	
	(Contd. of page 4)
TLV	Long-term value: 9.7 mg/m ³ , 1 ppm
08.0	Skin
	5-3 nitrobenzene
	Long-term value: 5 mg/m³, 1 ppm Skin
REL	Long-term value: 5 mg/m³, 1 ppm Skin
TLV	Long-term value: 5 mg/m³, 1 ppm Skin; BEI
87-8	6-5 pentachlorophenol
PEL	Long-term value: 0.5 mg/m ³ Skin
REL	Long-term value: 0.5 mg/m ³ Skin
TLV	Short-term value: 1* mg/m³ Long-term value: 0.5* mg/m³
	Skin; BEI;*inhalable fraction+vapor
	46-7 1,4-dichlorobenzene
	Long-term value: 450 mg/m³, 75 ppm
REL	See Pocket Guide App. A
TLV	Long-term value: 60 mg/m³, 10 ppm
· Ingr	edients with biological limit values:
75-0	9-2 dichloromethane
BEI	0.3 mg/L
	Medium: urine
	Time: end of shift Parameter: Dichloromethane (semi-quantitative)
98-9	5-3 nitrobenzene
BEI	5 mg/g creatinine
	Medium: urine
	Time: end of shift at end of workweek Parameter: Total p-nitrophenol (nonspecific)
	1.5 % of hemoglobin
	Medium: blood
	Time: end of shift Parameter: Mathemaclohin (background nonspecific sami quantitating)
	Parameter: Methemoglobin (background, nonspecific, semi-quantitative)
	6-5 pentachlorophenol
BEI	2 mg/g creatinine Medium: urine
	Time: prior to last shift of workweek
	Parameter: Total pentachlorophenol (background)
	5 mg/L
	Medium: plasma
	Time: end of shift
	Parameter: Free pentachlorophenol (background)
· Addi	itional information: The lists that were valid during the creation were used as basis.
	osure controls
· Pers	onal protective equipment:
	eral protective and hygienic measures: o away from foodstuffs, beverages and feed.
кеер Ітт	ediately remove all soiled and contaminated clothing.
Wasi	h hands before breaks and at the end of work.
Store	e protective clothing separately.
	d contact with the eyes and skin.
	piratory protection:
	ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is pendent of circulating air.
	(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection:
- Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

General Information Liquid Appearance: Equid Form: Liquid Color: According to product specification Odor: Characteristic Odour Threshold: Not applicable. • PH-value: Not applicable. • PH-value: Not applicable. • PH-value: Undetermined. Boiling point/Mcling range: 40 °C (104 °F) • Flash point: < 0 °C (<32 °F) • Flash point: < 0 °C (<32 °F) • Flash point: < 0 °C (<121 °F) • Decomposition temperature: Not applicable. • Jupier: Not applicable. • Jupier: Not applicable. • Jupier: Not applicable. • Jupier: Not applicable. • Lower: 13 Vol % Upper: 22 Vol % • Vapor ensure at 20 °C (68 °F): 43 Sh Pa (339.8 mm Hg) • Relative density Not applicable. • Vapor density Not applicable. • Vapor density Not applicable. • Vapor density Not applicable. • Solability in / Miscibility with <	· Information on basic physical and c	hemical properties	
i Form: Liquid Color: According to product specification Odour Threshold: Not applicable. i Oldour Threshold: Not applicable. offung point/Boiling range: Undetermined. Boiling point/Boiling range: Undetermined. Boiling point/Boiling range: 0 ° C (04 °F) · Flash point: < 0 ° C (<32 °F) · Flash point: < 0 ° C (<42 °F) · Flammability (solid, gaseous): Not applicable. · Jgnition temperature: 605 °C (1,121 °F) · Decomposition temperature: Not applicable. · June: Product is not selfigniting. · June: I or out is not selfigniting. · Laver: 13 Vol % Upper: 22 Vol % · Vapor pressure at 20 °C (68 °F): 453 NPa (339.8 mm Hg) · Vapor pressure at 20 °C (68 °F): 1.33251 g/cm² (11.1198 Ibs/gal) · Relative density Not applicable. · Vapor forsibility with Not applicable. · Vapor density <			
Color:According to product specificationOdor:CharacteristicOdor:Not applicable.>pH-value:Not applicable.>CharacteristicNot applicable.>CharacteristicUndetermined.Meiling point/Boiling range:Undetermined.Boiling point/Boiling range:Undetermined.Boiling point/Boiling range:Vot (104 °F)> Flash point:< 0 °C (32 °F)• Flash point:< 0 °C (1/21 °F)• Jenomability (solid, gaseous):Not applicable.• Jenomability (solid, gaseous):Not applicable.• Jenomability (solid, gaseous):Not applicable.• Jager of explosion:Product is not selfigniting.• Jawer:13 Vol %Upwer:13 Vol %Upwer:22 Vol %• Vaoor pressure at 20 °C (68 °F):453 shPa (339.8 nm Hg)• Not applicable.Not applicable.• Vapor densityNot applicable.• Vapor densityNot applicable.• Vaoor densityNot applicable.• Vapor densityNot applicable.• Solubility infNot applicable.• Vapor densityNot applicable.• Solubility information <th>· Appearance:</th> <th></th> <th></th>	· Appearance:		
• Odor: Characteristic • Odor: Threshold: Not applicable. • pH-value: Not applicable. • Other pein condition Undetermined. Melting point/Melting range: Undetermined. • Plashop int: < 0 °C (104 °F) • Flash point: < 0 °C (104 °F) • Flash point/Melting range: Mot applicable. • Ignition temperature: 605 °C (1,121 °F) • Decomposition temperature: Not applicable. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. • Explosion limits: 13 Vol % ⊥ ower: 13 Vol % Upper: 22 Vol % • Vapor pressure at 20 °C (68 °F) 453 hPa (339.8 mm Hg) • Density at 20 °C (68 °F) 1.33251 g/cm² (11.198 lbs/gal) • Relative density Not applicable. • Vapor pressure at 20 °C (68 °F) 1.33251 g/cm² (11.198 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Vapor density Not applicable. • Vapor ansity Not applica	Form:	Liquid	
· Odour Threshold:Not applicable.· pH-value:Not applicable.· PH-value:Vndetermined. 40 °C (104 °F)· Plans point/Boiling range:Undetermined. 40 °C (104 °F)· Flash point:< 0 °C (<32 °F)· Flash point:60 °C (<32 °F)· Jenition temperature:Not applicable.· Decomposition temperature:Not applicable.· Decomposition temperature:Not applicable.· Due on temperature:Not applicable.· Due on temperature:Not applicable.· Due on temperature:13 Vol % 22 Vol %· Auto igniting:13 Vol % 22 Vol %· Vapor pressure at 20 °C (68 °F):453 Ahe (339.8 mm Hg)· Due sity at 20 °C (68 °F):453 Ahe (339.8 mm Hg)· Due sity at 20 °C (68 °F):133251 g/cm² (11.1198 lb/gal) Not applicable.· Vapor densityNot applicable.· Vapor densityNot applicable.· Solubility in / Miscibility wilk Water:Not applicable.· Solubilit	Color:		
- PH-value: Not applicable. • Change in condition Melting point/Boiling range: Undetermined. Boiling point/Boiling range: 40 °C (104 °F) • Flash point: < 0 °C (<32 °F) • Flash point: < 0 °C (<121 °F) • Decomposition temperature: 605 °C (1,121 °F) • Decomposition temperature: Not applicable. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. • Explosion limits: I S Vol % Upper: 22 Vol % • Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) • Density at 20 °C (68 °F) 1.33251 g/cm ³ (11.1198 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Vapor density Not applicable. • Solubility in / Miscibility with Water: Not applicable. • Vasoritica (ficient (n-octanol/water): Not applicable. Not applicable. • Viscosity: Not applicable. • Vasoritica (n-octanol/water): Not applicable. Not applicable. • Viscosity: Not applicable. • Solubility in / Miscibility with Water:			
Change in condition Melting point/Boiling range: Undetermined. Boiling point/Boiling range: Undetermined. 40 °C (104 °F) Flash point: < 0 °C (<32 °F) Flammability (solid, gaseous): Not applicable. Ignition temperature: 605 °C (1,121 °F) Decomposition temperature: Not applicable. Auto igniting: Product is not selfigniting. Danger of explosion: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: I 3 Vol % Lower: 13 Vol % Upper: 22 Vol % Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) Density at 20 °C (68 °F) 1.33251 g/cm³ (11.1198 lbs/gal) Relative density Not applicable. Vapor density Not applicable. Evoporation rate Not applicable. Solubility in / Miscibility with Water: Not applicable. Viscosity: Dot applicable. Viscosity: Not applicable. Viscosity: Not applicable. Solvent content: Not applicable. Solvoftent (n-octanol/water): Not applicable. </th <th>· Odour Threshold:</th> <th>Not applicable.</th> <th></th>	· Odour Threshold:	Not applicable.	
Meining point/Melting range: Undetermined. 40°C (104°F) · Flash point: < 0°C (<32°F) · Flash point: < 0°C (<32°F) · Flammability (solid, gaseous): Not applicable. · Ignition temperature: < 00°C (<121°F) · Decomposition temperature: Not applicable. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. · Explosion limits: 13 Vol % · Upper: 13 Vol % · Upper: 13 Vol % · Upper: 22 Vol % · Vapor pressure at 20°C (68°F) 1.33251 g/cm³ (11.1198 lbs/gal) · Relative density Not applicable. · Explosion intert: Not applicable. · Vapor density Not applicable. · Vapor density Not applicable. · Solubility in / Miscibility with Not applicable. · Vapor density Not applicable. · Solubility in / Miscibility with Not applicable. · Solubility in / Miscibility with Not applicable. · Solubility in / Miscibility with Not applicable. · Solvent c	· pH-value:	Not applicable.	
• Flammability (solid, gaseous): Not applicable. • Ignition temperature: 605 °C (1,121 °F) • Decomposition temperature: Not applicable. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product is not selfigniting. • Danger of explosion limits: Is not explosive. However, formation of explosive air/vapor mixtures are possible. • Explosion limits: Is Not % Lower: 13 Vol % Upper: 22 Vol % • Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) • Density at 20 °C (68 °F): 1.33251 g/cm³ (11.1198 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Solubility in / Miscibility with Not applicable. • Solubility in / Miscibility with Not applicable. • Viscosity: Not applicable. • Viscosity: Not applicable. • Viscosity: Not applicable. • Viscosity: Not applicable. • Solvent content: Not applicable. • Solvent content: 07.8 % • Organic solvents: 97.8 % • VOC content: 0.80 % <th>Melting point/Melting range:</th> <th></th> <th></th>	Melting point/Melting range:		
Ignition temperature: 605 °C (1,121 °F) Decomposition temperature: Not applicable. Auto igniting: Product is not selfigniting. Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: Lower: 13 Vol % Upper: 22 Vol % Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) Density at 20 °C (68 °F): 1.33251 g/cm³ (11.1198 lbs/gal) Relative density Not applicable. Vapor density Not applicable. Solubility in / Miscibility with Not applicable. Viscosity: Not applicable. Dynamic: Not applicable. Viscosity: Not applicable. Opnamic: Not applicable. Solvent content: Or applicable. Solvent content: 0.80 %	· Flash point:	$< 0 \ ^{\circ}C \ (<32 \ ^{\circ}F)$	
• Decomposition temperature: Not applicable. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. • Explosion limits: Is vol % Lower: 13 Vol % Upper: 22 Vol % • Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) • Density at 20 °C (68 °F): 1.33251 g/cm³ (11.1198 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Solubility in / Miscibility with Water: Not applicable. • Viscosity: Dot miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not applicable. Not applicable. • Viscosity: Dynamic: Not applicable. • Solvent content: Not applicable. • Solvent content: 0.80 %	· Flammability (solid, gaseous):	Not applicable.	
• Auto igniting: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. • Explosion limits: I3 Vol % Lower: 13 Vol % Upper: 22 Vol % • Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) • Density at 20 °C (68 °F): 1.33251 g/cm³ (11.1198 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Vapor density Not applicable. • Solubility in / Miscibility with Water: Not miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not applicable. Not applicable. • Viscosity: Not applicable. • Dynamic: Not applicable. • Solvent content: Organic solvents: Organic solvents: 97.8 % • VOC content: 0.80 %	· Ignition temperature:	605 °C (1,121 °F)	
• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. • Explosion limits: Is Vol % Lower: 13 Vol % Upper: 22 Vol % • Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) • Density at 20 °C (68 °F): 1.33251 g/cm³ (11.1198 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Viscosity: Not miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not applicable. Not applicable. • Viscosity: Not applicable. Dynamic: Not applicable. • Solvent content: Or applicable. • Solvent content: 0.80 %	· Decomposition temperature:	Not applicable.	
• Explosion limits: 1 1 1 1 Lower: 13 Vol % 22 Vol % • Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) • Density at 20 °C (68 °F) 1.33251 g/cm³ (11.1198 lbs/gal) . Relative density Not applicable. • Vapor density Not applicable. • Evaporation rate Not applicable. • Solubility in / Miscibility with Water: Not miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not applicable. Not applicable. • Viscosity: Not applicable. Dynamic: Not applicable. • Solvent content: Organic solvents: Organic solvents: 97.8 % VOC content: 0.80 %	• Auto igniting:	Product is not selfigniting.	
Lower:13 Vol % 22 Vol %Vapor pressure at 20 °C (68 °F):453 hPa (339.8 mm Hg)• Density at 20 °C (68 °F):1.33251 g/cm³ (11.1198 lbs/gal) Not applicable.• Relative densityNot applicable.• Vapor densityNot applicable.• Vapor densityNot applicable.• Solubility in / Miscibility with Water:Not miscible or difficult to mix.• Partition coefficient (n-octanol/water): Not applicable.• Viscosity:Not applicable.• Dynamic: Kinematic:Not applicable.• Solvent content: Organic solvents:97.8 % 0.80 %	· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
Upper:22 Vol %· Vapor pressure at 20 °C (68 °F):453 hPa (339.8 mm Hg)· Density at 20 °C (68 °F)1.33251 g/cm³ (11.1198 lbs/gal)· Relative densityNot applicable.· Vapor densityNot applicable.· Vapor densityNot applicable.· Evaporation rateNot applicable.· Solubility in / Miscibility with Water:Not miscible or difficult to mix.· Partition coefficient (n-octanol/water): Not applicable.· Viscosity: Dynamic: Kinematic:Not applicable.· Solvent content: Organic solvents:97.8 % 0.80 %	· Explosion limits:		
· Vapor pressure at 20 °C (68 °F): 453 hPa (339.8 mm Hg) · Density at 20 °C (68 °F) 1.33251 g/cm³ (11.1198 lbs/gal) · Relative density Not applicable. · Vapor density Not applicable. · Vapor density Not applicable. · Vapor density Not applicable. · Solubility in / Miscibility with Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not applicable. Not applicable. · Viscosity: Not applicable. Dynamic: Not applicable. · Viscosity: Not applicable. · Solvent content: Not applicable. · Solvent content: 97.8 % · VOC content: 0.80 %	Lower:		
• Density at 20 °C (68 °F) 1.33251 g/cm³ (11.1198 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Evaporation rate Not applicable. • Solubility in / Miscibility with Water: Not miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not applicable. Not applicable. • Viscosity: Dynamic: Kinematic: Not applicable. • Solvent content: Organic solvents: 97.8 % VOC content: 0.80 % 0.80 %	Upper:	22 Vol %	
Relative densityNot applicable.Vapor densityNot applicable.Evaporation rateNot applicable.Solubility in / Miscibility with Water:Not miscible or difficult to mix.Partition coefficient (n-octanol/water):Not applicable.Viscosity: Dynamic: Kinematic:Not applicable.Solvent content: Organic solvents: 0.80 %97.8 %	\cdot Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)	
· Vapor density Not applicable. · Evaporation rate Not applicable. · Solubility in / Miscibility with Water: · Vater: Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not applicable.	· Density at 20 °C (68 °F)	1.33251 g/cm ³ (11.1198 lbs/gal)	
· Evaporation rate Not applicable. · Solubility in / Miscibility with Water: Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not applicable. · Viscosity: Dynamic: Kinematic: Not applicable. · Solvent content: Organic solvents: 97.8 % · VOC content: 0.80 %	· Relative density	Not applicable.	
· Solubility in / Miscibility with Water: Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not applicable. · Viscosity: Dynamic: Kinematic: Not applicable. · Viscosity: Dynamic: Not applicable. · Viscosity: Dynamic: Solvent content: Organic solvents: 97.8 % · VOC content: 0.80 %			
Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not applicable. Viscosity: Not applicable. Dynamic: Not applicable. Kinematic: Not applicable. Solvent content: 97.8 % Organic solvents: 97.8 % VOC content: 0.80 %	• Evaporation rate	Not applicable.	
• Viscosity: Not applicable. Dynamic: Not applicable. Kinematic: Not applicable. • Solvent content: 97.8 % • VOC content: 0.80 %		Not miscible or difficult to mix.	
Dynamic:Not applicable.Kinematic:Not applicable.Solvent content:97.8 %Organic solvents:97.8 %VOC content:0.80 %	· Partition coefficient (n-octanol/wate	r): Not applicable.	
Kinematic:Not applicable.Solvent content:97.8 %Organic solvents:97.8 %VOC content:0.80 %	· Viscosity:		
· Solvent content: 0rganic solvents: 97.8 % VOC content: 0.80 %		Not applicable.	
Organic solvents:97.8 %VOC content:0.80 %	Kinematic:	Not applicable.	
VOC content: 0.80 %			
	VOC content:	0.80 %	
(Contd. on p			(Contd. on page 7)

(Contd. of page 5)

Reviewed on 03/28/2018

Reviewed on 03/28/2018

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

Solids content: • Other information 2.0 % No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

• Conditions to avoid No further relevant information available.

 $\cdot \textit{Incompatible materials: } No further relevant information available.$

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

 \cdot Information on toxicological effects

· Acute toxicity:

· LD/LC50	values that	t are relevant for classification:
75-09-2 di	chloromet	hane
Oral	LD50	1,600 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/l (rat)
88-06-2 2,	4,6-trichlo	rophenol
Oral	LD50	820 mg/kg (rat)
121-14-2 2	2,4-dinitrot	oluene
Oral	LD50	268 mg/kg (rat)
111-44-4 l	ois(2-chlor	oethyl) ether
Oral	LD50	75 mg/kg (rat)
Dermal	LD50	90 mg/kg (rabbit)
Inhalative	LC50/4 h	0.33 mg/l (rat)
87-86-5 pe	ntachloro	phenol
Oral	LD50	27 mg/kg (rat)
Dermal	LD50	105 mg/kg (rat)
106-46-7	,4-dichlor	obenzene
Oral	LD50	500 mg/kg (rat)
· Additiona	n: No irrita : No irritat on: No sen l toxicologi ct shows th	int effect.

· Carcinogenic categories

· IARC (In	ternational Agency for Research on Cancer)	
75-09-2	dichloromethane	2A
95-95-4	2,4,5-trichlorophenol	2B
88-06-2	2,4,6-trichlorophenol	2B
121-14-2	2,4-dinitrotoluene	2B
111-44-4	bis(2-chloroethyl) ether	3
118-74-1	hexachlorobenzene	2B
87-68-3	hexachlorobuta-1,3-diene	3
67-72-1	hexachloroethane	2B
98-95-3	nitrobenzene	2B
87-86-5	pentachlorophenol	2B
108-95-2		3
110-86-1	Nitrogen (from Pyridine)	3
106-46-7	1,4-dichlorobenzene	2B
	(Con	td. on page 8)

Printing date 03/28/2018

Reviewed on 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

		(Contd. of page 7)
· NTP (Nat	tional Toxicology Program)	
	dichloromethane	R
88-06-2	2,4,6-trichlorophenol	R
118-74-1	hexachlorobenzene	R
67-72-1	hexachloroethane	R
98-95-3	nitrobenzene	R
	pentachlorophenol	R
106-46-7	1,4-dichlorobenzene	R
· OSHA-Ca	a (Occupational Safety & Health Administration)	
75-09-2 d	dichloromethane	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

- \cdot Results of PBT and vPvB assessment
- · PBT:

87-68-3 hexachlorobuta-1,3-diene

· vPvB:

87-68-3 hexachlorobuta-1,3-diene

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information · UN-Number UN1593 · DOT, ADR, IMDG, IATA · UN proper shipping name $\cdot DO\hat{T}$ Dichloromethane · ADR 1593 Dichloromethane · IMDG, IATA DICHLOROMETHANE · Transport hazard class(es) $\cdot DOT$ ŤOXIČ · Class 6.1 Toxic substances (Contd. on page 9) US

Printing date 03/28/2018

Reviewed on 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

	(Contd. of page 8
· Label	6.1
· ADR, IMDG, IATA	
· Class	6.1 Toxic substances
· Label	6.1
· Packing group · DOT, ADR, IMDG, IATA	111
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Toxic substances
· Danger code (Kemler):	60
· EMS Number:	F-A,S-A
· Segregation groups	Liquid halogenated hydrocarbons
· Stowage Category	A
• Transport in bulk according to Annex II of MARH	
Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
·IMDG	
\cdot Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1593 DICHLOROMETHANE, 6.1, III

15 Regulatory information

Sara Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
• TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
• TSCA new (21st Century Act) (Substances not listed)	
95-95-4 2,4,5-trichlorophenol	
88-06-2 2,4,6-trichlorophenol	
87-68-3 hexachlorobuta-1,3-diene	
· Proposition 65	
· Chemicals known to cause cancer:	
75-09-2 dichloromethane	
88-06-2 2,4,6-trichlorophenol	
121-14-2 2,4-dinitrotoluene	
111-44-4 bis(2-chloroethyl) ether	
118-74-1 hexachlorobenzene	
87-68-3 hexachlorobuta-1,3-diene	
67-72-1 hexachloroethane	
98-95-3 nitrobenzene	
87-86-5 pentachlorophenol	
110-86-1 Nitrogen (from Pyridine)	
106-46-7 1,4-dichlorobenzene	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
	(Contd. on page 1

- US

Reviewed on 03/28/2018

Printing date 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

		(Contd. of page 9)		
· Chemicals known to cause reproductive toxicity for males:				
	2,4-dinitrotoluene			
98-95-3	nitrobenzene			
· Chemicals known to cause developmental toxicity:				
118-74-1	hexachlorobenzene			
· Carcinogenic categories				
· EPA (En	vironmental Protection Agency)			
75-09-2	dichloromethane	L		
88-06-2	2,4,6-trichlorophenol	B2		
95-48-7	o-cresol	С		
108-39-4	3-Methylphenol	С		
106-44-5		С		
111-44-4	bis(2-chloroethyl) ether	B2		
118-74-1	hexachlorobenzene	B2		
87-68- <i>3</i>	hexachlorobuta-1,3-diene	С		
67-72-1	hexachloroethane	L		
98-95-3	nitrobenzene	L		
87-86-5	pentachlorophenol	L		
108-95-2	phenol	D, I		
· TLV (Th	eshold Limit Value established by ACGIH)			
	dichloromethane	A3		
111-44-4	bis(2-chloroethyl) ether	A4		
118-74-1	hexachlorobenzene	A3		
87-68-3	hexachlorobuta-1,3-diene	A3		
67-72-1	hexachloroethane	A3		
98-95-3	nitrobenzene	A3		
87-86-5	pentachlorophenol	A3		
108-95-2		A4		
106-46-7	1,4-dichlorobenzene	A3		
· NIOSH-0	a (National Institute for Occupational Safety and Health)			
75-09-2	dichloromethane			
121-14-2	2,4-dinitrotoluene			
111-44-4	bis(2-chloroethyl) ether			
87-68-3	hexachlorobuta-1,3-diene			
67-72-1	hexachloroethane			
106-46-7	1,4-dichlorobenzene			
CHELab	GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS)			

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: dichloromethane nitrobenzene bis(2-chloroethyl) ether 2,4-dinitrotoluene
Hazard statements H225 Highly flammable liquid and vapor. H302 Harmful if swallowed. H350 May cause cancer. H360 May damage fertility or the unborn child.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment. Wear protective gloves/protective clothing/eye protection/face protection.

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2018

Product Name: TCLP Calibration/Spiking Mix

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

- · Contact:
- SPEX CertiPrep, LLC. 1-732-549-7144
- · Date of preparation / last revision 03/28/2018 / -
- · Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation
- IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety OSHA: Occupational Institute for Occupation OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

- REL: Recommended Exposure Limit

- BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids Category 2 Acute Tox. 4: Acute toxicity Category 4 Carc. 1B: Carcinogenicity Category 1B
- Repr. 1: Reproductive toxicity Category 1

(Contd. of page 10)

Reviewed on 03/28/2018