

Safety Data Sheet acc. to OSHA HCS

Printing date 02/28/2023

1 Identification

- · Product identifier
- · Product Name: BTEX Characterized Gasoline Standard
- · Part Name: GAS-20
- · Application of the substance / the mixture Certified Reference Material
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Spex CertiPrep, LLC.
 203 Norcross Ave, Metuchen, NJ 08840 USA
 732-549-7144
 USMet-CRMSales@antylia.com
- · Information department: product safety department
- Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet acc. to OSHA HCS

certipren Printing date 02/28/2023

Product Name: BTEX Characterized Gasoline Standard

| P303+P361+P3 | 353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
|------------------|---|
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P321 | Specific treatment (see on this label). |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Classification s | nstom · |

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

| Dangerous compo |
|-------------------------------------|
|-------------------------------------|

| · Dangerous components: | | |
|-------------------------|------|----|
| 67-56-1 methanol | 98.0 | 0% |
| 86290-81-5 Gasoline | 2.0 | % |
| | | |

4 First-aid measures

- · Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.
- Remove breathing apparatus only after contaminated clothing have been completely removed.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- · After inhalation:
- Supply fresh air or oxygen; call for doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. of page 1)

Reviewed on 02/28/2023

Product Name: BTEX Characterized Gasoline Standard

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

| • PAC-1: | |
|---------------------|-----------|
| 67-56-1 methanol | 530 ppm |
| 86290-81-5 Gasoline | 200 ppm |
| • PAC-2: | |
| 67-56-1 methanol | 2,100 ppm |
| 86290-81-5 Gasoline | 1,000 ppm |
| • PAC-3: | |
| 67-56-1 methanol | 7200* ppm |
| 86290-81-5 Gasoline | 4000* ppm |

Safety Data Sheet

acc. to OSHA HCS

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities • Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

| · Additional information | about design | of technical sv | stems: No further | data; see item 7. |
|--------------------------|--------------|-----------------|-------------------|-------------------|
| | | | | |

· Control parameters

| ·Com | roi parameters | |
|---------|---|--------------------|
| · Comp | ponents with limit values that require monitoring at the workplace: | |
| 67-56 | 5-1 methanol | |
| PEL | Long-term value: 260 mg/m ³ , 200 ppm | |
| | Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin | |
| | Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI | |
| 8629 | 0-81-5 Gasoline | |
| REL | See Pocket Guide App. A | |
| | Short-term value: 500 ppm Long-term value: 300 ppm A3 | |
| · Ingre | rdients with biological limit values: | |
| 67-56 | 5-1 methanol | |
| 1 | 15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific) | |
| | | (Contd. on page 4) |

Reviewed on 02/28/2023

(Contd. of page 2)

Printing date 02/28/2023

Product Name: BTEX Characterized Gasoline Standard

(Contd. of page 3)

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Safety Data Sheet

acc. to OSHA HCS

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

| · Information on basic physical and o · General Information | chemical properties |
|--|--|
| · Appearance: | |
| Form: | Liquid |
| Color: | According to product specification |
| · Odor: | Characteristic |
| · Odour Threshold: | Not applicable. |
| · pH-value: | Not applicable. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 64.7 °C (148.5 °F) |
| · Flash point: | $< 23 \ ^{\circ}C \ (< 73.4 \ ^{\circ}F)$ |
| · Flammability (solid, gaseous): | Highly flammable. |
| · Ignition temperature: | 455 °C (851 °F) |
| • Decomposition temperature: | Not applicable. |
| · Auto igniting: | Product is not selfigniting. |
| • Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 5.5 Vol % |
| Upper: | 44 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 128 hPa (96 mm Hg) |
| · Density | Not applicable. |
| · Relative density | Not applicable. |
| · Vapor density | Not applicable. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with | |
| Water: | Fully miscible. |
| · Partition coefficient (n-octanol/wat | er): Not annlicable. |

Page 5/8

Product Name: BTEX Characterized Gasoline Standard

| | (Contd. c | of page 4) |
|---------------------|--|------------|
| · Viscosity: | | |
| Dynamic: | Not applicable. | |
| Kinematic: | Not applicable. | |
| · Solvent content: | | |
| Organic solvents: | 98.0 % | |
| VOC content: | 98.00 % | |
| Solids content: | 0.0 % | |
| • Other information | No further relevant information available. | |
| | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC50 val | ues that are re | levant for | classification: |
|---------------|-----------------|------------|-----------------|
| | | | |

| 67-56-1 methanol |
|------------------|
|------------------|

- LD50 5,628 mg/kg (rat) Oral
- Dermal LD50 15,800 mg/kg (rabbit)
- · Primary irritant effect:
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations:
- Toxic

The product can cause inheritable damage.

· Carcinogenic categories

| IARC | (International Agency for Research on | (Cancer) |
|-------|---------------------------------------|------------|
| ·IAAC | (International Agency for Research on | (cuncer) |

86290-81-5 Gasoline

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

2B

Product Name: BTEX Characterized Gasoline Standard

Reviewed on 02/28/2023

(Contd. of page 5)

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Safety Data Sheet acc. to OSHA HCS

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

| 14 Transport information | |
|--|--|
| · UN-Number · DOT, ADR, IMDG, IATA | UN1230 |
| UN proper shipping name DOT ADR IMDG, IATA | Methanol 1230 METHANOL METHANOL |
| · Transport hazard class(es) | |
| · DOT | 3 Flammable liquids |
| · Label | 3, 6.1 |
| · ADR | |
| · Class · Label | 3 Flammable liquids 3+6.1 |
| · IMDG | |
| | |
| · Class · Label | 3 Flammable liquids 3/6.1 |
| | |
| · Class · Label | 3 Flammable liquids 3 (6.1) |
| Packing group DOT, ADR, IMDG, IATA | II |
| · Environmental hazards: | Not applicable. |
| Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Stowage Code | Warning: Flammable liquids 336 F-E,S-D B SW2 Clear of living quarters. |
| • Transport in bulk according to Annex II of MARPOL73/78 and | the IBC Code Not applicable. |

Page 7/8

Product Name: BTEX Characterized Gasoline Standard

| (Contd. of page 6 |
|--|
| |
| |
| Code: E2 |
| Maximum net quantity per inner packaging: 30 ml |
| Maximum net quantity per outer packaging: 500 ml |
| |
| 1L |
| Code: E2 |
| Maximum net quantity per inner packaging: 30 ml |
| Maximum net quantity per outer packaging: 500 ml |
| UN 1230 METHANOL, 3 (6.1), II |
| |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. · Sara

| · Sara | |
|--|--------|
| • Section 313 (Specific toxic chemical listings): | |
| 67-56-1 methanol | |
| · TSCA (Toxic Substances Control Act): | |
| 67-56-1 methanol | ACTIVE |
| · Hazardous Air Pollutants | |
| 67-56-1 methanol | |
| · Proposition 65 | |
| · Chemicals known to cause cancer: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for females: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause developmental toxicity: | |
| 67-56-1 methanol | |
| · Carcinogenic categories | |
| · EPA (Environmental Protection Agency) | |
| None of the ingredients is listed. | |
| · TLV (Threshold Limit Value) | |
| 86290-81-5 Gasoline | A3 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | |
| 86290-81-5 Gasoline | |

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: methanol Gasoline · Hazard statements H225 Highly flammable liquid and vapor. H331 Toxic if inhaled. H340 May cause genetic defects. H351 Suspected of causing cancer.

H370 Causes damage to the central nervous system and the visual organs.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Ground/bond container and receiving equipment. P240
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.

Printing date 02/28/2023

Reviewed on 02/28/2023

Product Name: BTEX Characterized Gasoline Standard

(Contd. of page 7)

Page 8/8

US —

| P242 Use only non-sparking tools. | |
|--|--|
| P243 Take precautionary measures against static discharge. | |
| P260 Do not breathe dust/fume/gas/mist/vapors/spray. | |
| P280 Wear protective gloves/protective clothing/eye protection/face protection. | |
| P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. | |
| <i>P304+P340</i> IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |
| P308+P313 IF exposed or concerned: Get medical advice/attention. | |
| P321 Specific treatment (see on this label). | |
| P403+P233 Store in a well-ventilated place. Keep container tightly closed. | |
| P403+P235 Store in a well-ventilated place. Keep cool. | |
| P405 Store locked up. | |
| <i>P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</i> | |
| · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. | |

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department · Contact: Spex CertiPrep, LLC. 1-732-549-7144 · Date of preparation / last revision 02/28/2023 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Frammable Liquids 2: Frammable liquids – Category 2
Acute Toxicity - Inhalation 3: Acute toxicity – Category 3
Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B
Carcinogenicity 2: Carcinogenicity – Category 2
Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1