

Printing date 07/24/2023


Safety Data Sheet acc. to OSHA HCS

Page 1/8

1 Identification

- · Product identifier
- · Product Name: Ethanol
- Part Name: S-1885
- · Application of the substance / the mixture Certified Reference Material
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier:
 Spex CertiPrep, LLC.
 203 Norcross Ave, Metuchen,
 NJ 08840 USA
 732-549-7144
 USMet-CRMSales@antylia.com
- Information department: product safety department Emergency telephone number:
- Emergency Phone Number (24 hours)
- CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification



· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet acc. to OSHA HCS

Reviewed on 07/24/2023

Printing date 07/24/2023

Product Name: Ethanol

(Contd. of page 1)

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



Fire = 3Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
67-56-	l methanol	99.9%
64-17-3	5 ethanol	0.1%

4 First-aid measures

- · Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.
- Remove breathing apparatus only after contaminated clothing have been completely removed.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- · After inhalation:
- Supply fresh air or oxygen; call for doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.
- 5 Fire-fighting measures
- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:
- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Printing date 07/24/2023

Product Name: Ethanol

certipren

Reviewed on 07/24/2023

ouuci Nume. Einunoi	
Dispose contaminated material as waste according to section 13.	

- Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information. • Protective Action Criteria for Chemicals

Totecuve Action Crueria for Chemicais		
· PAC-1:		
67-56-1 methanol	530 ppm	
64-17-5 ethanol	1,800 ppm	
· PAC-2:		
67-56-1 methanol	2,100 ppm	
64-17-5 ethanol	3300* ppm	
· PAC-3:		
67-56-1 methanol	7200* ppm	
64-17-5 ethanol	15000* ppm	
	•	

7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles. • Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:	
67-56-1 methanol	
PEL Long-term value: 260 mg/m ³ , 200 ppm	
REL Short-term value: 325 mg/m ³ , 250 ppm	
Long-term value: 260 mg/m³, 200 ppm Skin	
TLV Short-term value: 250 ppm	
Long-term value: 200 ppm	
Skin; BEI	
64-17-5 ethanol	
PEL Long-term value: 1900 mg/m³, 1000 ppm	
REL Long-term value: 1900 mg/m ³ , 1000 ppm	
TLV Short-term value: 1000 ppm	
A3	
Ingredients with biological limit values:	
67-56-1 methanol	
BEI 15 mg/L	
Medium: urine	
Time: end of shift	
Parameter: Methanol (background, nonspecific)	
· Additional information: The lists that were valid during the creation were used as basis.	
	(Contd on page 4)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Reviewed on 07/24/2023

Product Name: Ethanol

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work. Store protective clothing separately.
- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

• Information on basic physical and o • General Information	hemical properties
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odour Threshold:	Not applicable.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)
· Flash point:	< 23 °C (< 73.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	455 °C (851 °F)
• Decomposition temperature:	Not applicable.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
· Density at 20 °C (68 °F)	0.79 g/cm ³ (6.59255 lbs/gal)
· Relative density	Not applicable.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/wat	pr) · Not annlicable

(Contd. on page 5)

(Contd. of page 3)



Page 5/8

Product Name: Ethanol

	(Contd. of page 4)
Not applicable.	
Not applicable.	
100.0 %	
100.00 %	
0.0 %	
No further relevant information available.	
	Not applicable. 100.0 % 100.00 % 0.0 %

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- \cdot Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

 · LD/LC50 values that are relevant for classification:

 67-56-1 methanol

 Oral
 [LD50] 5,628 mg/kg (rat)

Dermal LD50 15,800 mg/kg (rabbit)

· Primary irritant effect:

· on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

64-17-5 ethanol
• NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

• Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

1

Product Name: Ethanol

- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 07/24/2023

(Contd. of page 5)

14 Transport information · UN-Number · DOT, ADR, IMDG, IATA UN1230 · UN proper shipping name Methanol $\cdot DOT$ $\cdot ADR$ 1230 METHANOL · IMDG, IATA METHANOL · Transport hazard class(es) $\cdot DOT$ · Class 3 Flammable liquids 3, 6.1 · Label · ADR 3 Flammable liquids · Class · Label 3+6.1· IMDG · Class 3 Flammable liquids 3/6.1 · Label · IATA 3 Flammable liquids · Class · Label 3 (6.1) · Packing group · DOT, ADR, IMDG, IATA Π Not applicable. · Environmental hazards: · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 336 · EMS Number: F-E,S-D· Stowage Category В · Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · ADR Code: E2 \cdot Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 7)

⁻ US -



Page 7/8

(Contd. of page 6)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1230 METHANOL, 3 (6.1), II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara
· Section 313 (Specific toxic chemical listings):
67-56-1 methanol
· TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
· Hazardous Air Pollutants
67-56-1 methanol
· Proposition 65
· Chemicals known to cause cancer:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
· Chemicals known to cause developmental toxicity:
All ingredients are listed.
· Carcinogenic categories

5 5	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value)	
64-17-5 ethanol	A3
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the incredients is listed	

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labeling:
- methanol ethanol
- · Hazard statements
- H225 Highly flammable liquid and vapor.
- H331 Toxic if inhaled.
- H350 May cause cancer.

H370 Causes damage to the central nervous system and the visual organs.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.



Printing date 07/24/2023

Product Name: Ethanol

Page 8/8

US

Reviewed on 07/24/2023

(Contd. of page 7)

P321 P403+P233 P403+P235	Specific treatment (see on this label). Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

· Contact:

Spex CertiPrep, LLC. 1-732-549-7144 · Date of preparation / last revision 07/24/2023 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Inhalation 3: Acute toxicity – Category 3 Carcinogenicity IA: Carcinogenicity – Category IA Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1