Page 1/8

# **1** Identification

- · Product identifier
- · Product Name: Regular Unleaded Gasoline, 75% Weathered
- · Part Number: S-WG-75
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet · Manufacturer/Supplier: SPEX CertiPrep, LLC. 203 Norcross Ave, Metuchen, NJ 08840 USA
- · Information department: product safety department · Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

## 2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

H340 May cause genetic defects. Muta. 1B

Carc. 1B H350 May cause cancer.

STOT SE 1 H370 Causes damage to organs.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:
- methanol
- Gasoline
- · Hazard statements
- H225 Highly flammable liquid and vapor.
- H331 Toxic if inhaled.
- H340 May cause genetic defects. H350 May cause cancer.
- H370 Causes damage to organs.
- · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

- Use explosion-proof electrical/ventilating/lighting/equipment.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 09/11/2017

Reviewed on 09/11/2017

### Product Name: Regular Unleaded Gasoline, 75% Weathered

· Classification system: · NFPA ratings (scale 0 - 4)	(Contd. of page 1)
3 0 Health = 3 Fire = 3 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH*3FIRE3Fire = 3REACTIVITY $0$	
• Other hazards • Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.	

#### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
67-56-1	methanol	99.5%
86290-81-5	Gasoline	0.5%

### 4 First-aid measures

#### · Description of first aid measures

· General information:

- Immediately remove any clothing soiled by the product.
- Remove breathing apparatus only after contaminated clothing have been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration.
- · After inhalation:
- Supply fresh air or oxygen; call for doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

# 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- $\cdot$  Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents

(Contd. on page 3)

US

Reviewed on 09/11/2017

#### Product Name: Regular Unleaded Gasoline, 75% Weathered

• <b>Reference to other sections</b> See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.	(Contd. of page 2)
· Protective Action Criteria for Chemicals	
· PAC-1:	
67-56-1 methanol	530 ppm
86290-81-5 Gasoline	200 ppm
· PAC-2:	
67-56-1 methanol	2,100 ppm
86290-81-5 Gasoline	1,000 ppm
• PAC-3:	
67-56-1 methanol	7200* ppm
86290-81-5 Gasoline	4000* ppm

## 7 Handling and storage

- · Handling:
- $\cdot$  Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

	Control pur unicicity		
· Com	ponents with limit values that require monitoring at the workplace:		
67-5	6-1 methanol		
PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm		
REL	Short-term value: 325 mg/m³, 250 ppm		
	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm		
	Skin		
TLV	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm		
	Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI		
9(2)			
	0-81-5 Gasoline		
REL	See Pocket Guide App. A		
TLV	Short-term value: 1480 mg/m <sup>3</sup> , 500 ppm		
	Long-term value: 890 mg/m <sup>3</sup> , 300 ppm		
	bulk handling		
· Ingr	edients with biological limit values:		
67-5	6-1 methanol		
BEI	15 mg/L		
	Medium: urine		
	Time: end of shift		
	Parameter: Methanol (background, nonspecific)		
· Addi	tional information: The lists that were valid during the creation were used as basis.		
	(Contd. on page 4)		
	I		

#### Product Name: Regular Unleaded Gasoline, 75% Weathered

(Contd. of page 3)

Reviewed on 09/11/2017

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately. Avoid contact with the eyes and skin.
- Avoia contact with the eyes
- Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

<ul> <li>Information on basic physical and o</li> <li>General Information</li> </ul>	shemical properties
· Appearance:	
Form: Color:	Liquid According to product specification
· Odor:	Characteristic
· Odour Threshold:	Not applicable.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
<b>Boiling point/Boiling range:</b>	64.7 °C (148 °F)
· Flash point:	11 °C (52 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	455 °C (851 °F)
· Decomposition temperature:	Not applicable.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
• Explosion limits:	
Lower:	5.5 Vol %
Upper:	44.0 Vol %
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
· Density at 20 °C (68 °F)	0.79 g/cm <sup>3</sup> (6.593 lbs/gal)
· Relative density	Not applicable.
· Vapor density	Not applicable.
• Evaporation rate	Not applicable.

Printing date 09/11/2017

Reviewed on 09/11/2017

#### Product Name: Regular Unleaded Gasoline, 75% Weathered

		(Contd. of page 4)	
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.		
· Partition coefficient (n-octanol/w	Partition coefficient (n-octanol/water): Not applicable.		
· Viscosity:			
Dynamic:	Not applicable.		
Kinematic:	Not applicable.		
· Solvent content:			
Organic solvents:	99.5 %		
VOC content:	99.5 %		
Solids content:	0.5 %		
• Other information	No further relevant information available.		

#### **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11** Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

67-56-1 methanol

Oral LD50 5628 mg/kg (rat)

Dermal LD50 15800 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

• IARC (International Agency for Research on Cancer) 86290-81-5 Gasoline

#### Gustinic

 $\cdot$  NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- $\cdot$  Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

2B

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2017

Product Name: Regular Unleaded Gasoline, 75% Weathered

(Contd. of page 5)

Reviewed on 09/11/2017

• *Results of PBT and vPvB assessment* • *PBT:* Not applicable.

vPvB: Not applicable.
Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number	
· DOT, ADR, IMDG, IATA	UN1230
· UN proper shipping name · DOT	Methanol
·ADR	1230 Methanol
· IMDG, IATA	METHANOL
· Transport hazard class(es)	
·DOT	
RAMMARE LIGHT	
· Class · Label	3 Flammable liquids 3, 6.1
·ADR	
· Class	3 Flammable liquids
· Label	3+6.1
· Class	3 Flammable liquids
·Label	3/6.1
·IATA	
·Class	3 Flammable liquids
·Label	3 (6.1)
· Packing group · DOT, ADR, IMDG, IATA	11
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	336 F-E,S-D
· EMS Number: · Stowage Category	<i>Р-Е,</i> 5-D В
5 ···· 5. V	(Contd. on page 7)

Printing date 09/11/2017

Reviewed on 09/11/2017

# Product Name: Regular Unleaded Gasoline, 75% Weathered

	(Contd. of page 6)
· Stowage Code	SW2 Clear of living quarters.
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	IL Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1230 METHANOL, 3 (6.1), II

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	
· Sara	
Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
67-56-1 methanol	
· TSCA (Toxic Substances Control Act):	
67-56-1 methanol	
Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
67-56-1 methanol	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value established by ACGIH)	
86290-81-5 Gasoline	A3
·NIOSH-Ca (National Institute for Occupational Safety and Health)	
86290-81-5 Gasoline	
<b>CHS label alements</b> The product is classified and labeled according to the Globally Harmonized System (GHS)	

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

• Hazard-determining components of labeling: methanol

Gasoline • **Hazard statements** H225 Highly flammable liquid and vapor. H331 Toxic if inhaled. H340 May cause genetic defects. H350 May cause cancer.

US

#### Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2017

#### Product Name: Regular Unleaded Gasoline, 75% Weathered

Reviewed on 09/11/2017

H370 Causes damage to organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Do not breathe dust/fume/gas/mist/vapors/spray.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

· Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

· Date of preparation / last revision 09/11/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity – Category 3

Muta. 1B: Germ cell mutagenicity – Category 1B Carc. 1B: Carcinogenicity – Category 1B

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

(Contd. of page 7)